

industriële en decoratieve vloerafwerkingen

coatings voor beton en staal

HIM Products B.V. Maxwellstraat 2

1976 AD IJmuiden

• <u>www.him.nl</u> tel. 0251 276 300

slijtlagen voor brugdekken en andere constructies

<u>info@him.nl</u>

# **HIM Cleaner** Powerful cleaner for HIM flooring systems

#### Use

**HIM Cleaner** is a water based, very effective cleaning and degreasing agent for HIM flooring systems and coatings. **HIM Cleaner** is used for daily cleaning of the floor, but may also be used in case of strong decontamination. For extreme contamination **HIM Stain Remover** is available as a spray.

#### Product description

**HIM Cleaner** removes dirt, oil, grease, soot, shoe and tyre marks rapidly and effectively. This alkaline cleaner does not contain soap.

#### Advantages

- Biodegradable
- Perfectly safe for all HIM flooring systems
- Approved for use in the food iundustry
- Can be used to clean ESD floors like HIM SL Conductive (AS)
- Low foaming level
- Colors

## HIM Cleaner is red.

#### **Cleaning advice HIM Flooring systems**

Before using **HIM Cleaner** consult the extensive "Cleaning Advice *HIM flooring systems"*.

# Dosage and pH-value at 20°C

|             | Normal contamination                                        | Strong<br>contamination                                  | Extreme<br>contamination | pH-value at<br>20°C at mix<br>ratio cleaner :<br>water     |
|-------------|-------------------------------------------------------------|----------------------------------------------------------|--------------------------|------------------------------------------------------------|
| HIM Cleaner | 0,1 liter diluted<br>with 10 liter<br>cold or warm<br>water | 0,2 liter diluted<br>with 10 liter cold<br>or warm water | Use HIM Stain<br>Remover | 1 : 2 = 9,8<br>1 : 5 = 9,5<br>1 : 10 = 9,2<br>1 : 20 = 8,8 |



industriële en decoratieve vloerafwerkingen

slijtlagen voor brugdekken en andere constructies

coatings voor beton en staal

1976 AD IJmuiden

tel. 0251 276 300

#### Working temperature

**HIM Cleaner** is diluted with cold or warm water. The temperature of the water should not exceed 50°C.

#### New resin floors

We advise you to wait 7 days (at 20°C) before cleaning the floor for the first time. After 7 days the floor is completely cured.

#### **Cleaning equipment**

**HIM Cleaner** can be used with a doodlebug as well as with a scrubber or disc scrubber.

#### Storage conditions

Store **HIM Cleaner** in the original packaging at temperatures between 5°C and 25°C. Do not expose to temperatures below 0°C.

#### Safety precautions

Consult the material safety datasheet for additional information.

## Flash points

N.A.

#### Disposal

Disposal of spillage or empty packaging should be in accordance with local waste disposal regulations. For further information refer to the Material Safety Data Sheet.